

SAS SludgeTreat[™] 256SC

Product Data Sheet

Use in:

- Crude Oil SludgeTreatment
- Refinery Waste Treatment
- Tank BottomTreatment
- Oil Recovery



Product Description:

SAS SludgeTreat 256SC is for use in onshore waste management operations for the fast and safe treatment of crude oil sludge, refinery waste and heavy viscous tank bottom.

Benefits of using SAS SludgeTreat 256SC are:

Recovers virtually all oil

Reduces waste treatment times by at least 50%

Reduces waste volumes by up to 95%


SAS SludgeTreat 256SC does not form difficult to handle emulsion waste streams. The chemistry works by splitting emulsions into three separate fractions of oil, water and solids without the need to use thermal treatment processing, which can be expensive and hazardous to the environment.

From left to right:
1-Blank 2-SAS 156SC 3-SAS 256SC

How to use SAS SludgeTreat 256SC

1. Add SAS SludgeTreat 256SC to the oil slop or sludge. Dose circa 0.1% – 1% by weight.
2. Mix by agitation, stirring or chemical injection into the waste stream.
3. Collect waste after dosing and allow waste to separate out under gravity or through centrifugation.
4. Recover oil, send solids fit to landfill and send water to waste water treatment plant.

Note: SAS SludgeTreat 256SC can be used to reduce viscosity of heavy crude oils and mobilize solid waste streams.



Health & Safety

SAS SludgeTreat 256SC is safe for handling and no special procedures need be observed. SAS SludgeTreat 256SC is non flammable, non corrosive, non toxic and readily biodegradable.

Technical Information

SAS SludgeTreat 256SC is temperature insensitive and can be used at temperatures in the range of 5°C up to 100°C.

SAS SludgeTreat 256SC does not form oil/water emulsion waste which minimises waste production. After use, clean solids separate out under gravity or via centrifugation and can be sent to landfill. Oil can be recovered from the surface. Waste water can go to a waste water treatment plant for disposal.

Physical & Chemical Properties

Physical & Chemical Properties	
Appearance / Colour	Clear Liquid
Solubility	Soluble in Water
Odour	Characteristic
Specific Gravity	0.95 – 1.05 @ 20°C
pH Value	8.0 – 11.0
Flash Point	>85C
Flammability	Non Flammable
Biodegradability	Readily Biodegradable
Recommended Concentration	0.1% – 1% by Weight

Storage

Storage of all chemicals and protective clothing should be used as specified in the product SDS.

SAS SludgeTreat 256SC is stable for a period of up to 2 year provided it is stored and handled as specified in the product SDS.

Shipping & Packaging

SAS SludgeTreat 256SC is manufactured in the UK under ISO 9001:2008 and ISO 14001:2004 Quality, Environmental and Safety Management System Standards. Our minimum order quantity is one shipping pallet. The product is supplied in 40 x 25 kg containers, in 4 x 200 kg drums and in 1000 kg IBCs or 16 metric tonne bulk containers.

Product Volume	Product Code
1,000kg (40 x 25 kg Containers)	SludgeTreat 256SC – 40x25
800kg (4 x 200 kg Drums)	SludgeTreat 256SC – 4x200
1,000 kg IBC	SludgeTreat 256SC – 1000
16 IBC Full Container	SludgeTreat 256SC – 16MT

Contact us

To enquire about SASES products email us at

info@sasenvironment.com

or visit our website at

www.sasenvironment.com

UK Office:

Fairways Business Park
8 Deer Park Livingston,
EH54 8AF, UK

Tel: +44-(0) 1506 668 287

USA Office:

16225 Park Ten Place,
Suite 500,
Houston, Texas 77084

Tel: 281.213.0181